

SENSATA TECHNOLOGIES (BAOYING) CO., LTD.

KLIXON DEVICE OPERATING TEMPERATURE

| | |
|------------------------|-----------------------|
| DEVICE | <u>1NT011-4505</u> |
| LOT NUMBER | <u>3982153-9</u> |
| TEMP TEST AIR TANK | <u>9th</u> |
| OPEN TEMP LOW LIMIT | <u>71.1</u> |
| OPEN TEMP HIGH LIMIT | <u>76.7</u> |
| CLOSE TEMP LOW LIMIT | <u>47.2</u> |
| CLOSE TEMP HIGH LIMIT | <u>56.1</u> |
| RAMP RATE (DEGREE/MIN) | <u>1.50</u> |
| SOAK TIME (MINUTES) | <u>5.0</u> |



| UNIT | OPEN TEMP(C) | CLOSE TEMP(C) | MARKING CHECK | UNIT | OPEN TEMP(C) | CLOSE TEMP(C) | MARKING CHECK |
|------|--------------|---------------|---------------|------|--------------|---------------|---------------|
| 1 | 74.8 | 49.3 | | 17 | 75.6 | 48.0 | |
| 2 | 73.9 | 50.2 | | 18 | 74.8 | 49.1 | |
| 3 | 73.7 | 50.7 | | 19 | 75.2 | 48.8 | |
| 4 | 73.6 | 49.0 | | 20 | 74.8 | 48.2 | |
| 5 | 74.3 | 48.1 | | 21 | 74.5 | 48.0 | |
| 6 | 74.4 | 48.7 | | 22 | 74.1 | 49.0 | |
| 7 | 73.8 | 49.0 | | 23 | 72.9 | 48.1 | |
| 8 | 74.2 | 49.3 | | 24 | 74.8 | 51.1 | |
| 9 | 75.2 | 48.1 | | 25 | 75.0 | 49.3 | |
| 10 | 75.0 | 49.1 | | 26 | 74.2 | 50.0 | |
| 11 | 73.8 | 48.8 | | 27 | 74.0 | 50.0 | |
| 12 | 75.4 | 48.6 | | 28 | 73.0 | 50.0 | |
| 13 | 74.8 | 47.7 | | 29 | 74.6 | 50.1 | |
| 14 | 74.9 | 48.1 | | 30 | 74.9 | 50.5 | |
| 15 | 75.4 | 48.1 | | 31 | 74.3 | 50.2 | |
| 16 | 74.4 | 49.2 | | 32 | 73.9 | 49.9 | |